(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



A NATIO BENITADO O BERNIO DERI BANK BERNI DEN LO RIVERNA DE RESENTADO DE REPUBLICA DE LA COMPANIO DE REPUBLICAD

(43) International Publication Date 28 April 2005 (28.04.2005)

PCT

(10) International Publication Number WO 2005/039097 A1

(51) International Patent Classification7: H04Q 7/38

H04L 1/16,

(21) International Application Number:

PCT/JP2004/015650

- (22) International Filing Date: 15 October 2004 (15.10.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2003905712

17 October 2003 (17.10.2003)


- (71) Applicant (for all designated States except US): NEC CORPORATION [JP/JP]; 7-1, Shiba 5-chome, Minato-ku, Tokyo 108-8001 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): NGUYEN, Phong

[AU/AU]; c/o NEC Australia Pty. Ltd., 635 Ferntree Gully Road, Glen Waverley, VIC 3150 (AU).

- (74) Agent: MARUYAMA, Takao; Maruyama Patent Office, SAM Build., 3 Floor, 38-23, Higashi-Ikebukuro 2-chome, Toshima-ku, Tokyo 170-0013 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: ARQ CONTROL IN AN HSDPA COMMUNICATIONS SYSTEM



(57) Abstract: A method of Automatic Repeat reQuest (ARQ) control in a High Speed Downlink Packet Access (HSDPA) communication system. The method includes transmitting (300) control information from a first station to a second station; commencing receipt (312) of the control information at the second station; checking (502) whether the control information was received with error; and if so, generating (604) a negative acknowledgment (NACK) message for transmission to the first station. The control information error checking and acknowledgment message generating is performed at the second station by carrying out processing operations within radio interface layer 1 (UE layer 1).

WO 2005/039097 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.